

KLEERBLUE DRUM & TOTE PUMPS

Accu-Flo



Which Pump Is Right for Me?

| | CLOSED TOTE/IBC | OPEN TOTE/IBC | CLOSED DRUM | OPEN DRUM |
|---------------------------|-----------------|---------------|-------------------------------|-------------------------------|
| | | | | |
| | PG. 43 | PG. 44 | PG. 45 | PG. 46 |
| BENEFITS | | | | |
| Contaminant Resistant | ✓ | - | ✓ | - |
| Automatic Shut-Off Nozzle | Electric Only | Electric Only | Electric Only | Electric Only |
| Built-In Timer | 110 V | 110 V | 110 V | 110 V |
| | | | | |
| POWER REQUIREMENTS | | | | |
| 110 Volt | \checkmark | ✓ | ✓ | - |
| 12 Volt | ✓ | ✓ | ✓ | - |
| Air-Driven | - | - | - | ✓ |
| Hand-Pump | ✓ | - | ✓ | ✓ |
| Gravity | - | ✓ | - | ✓ |
| | | | | |
| GPM | | | | |
| 8 GPM | ✓ | ✓ | ✓ | ✓ |
| 6 GPM | - | - | - | ✓ |
| Manual | ✓ | ✓ | ✓ | ✓ |
| | | | | |
| ACCESSORIES | | | | |
| Meter Available | ✓ | Electric Only | Electric Only | - |
| 25' Hose | ✓ | - | Optional with Drum Trolley | Optional with Drum Trolley |
| 20' Hose | ✓ | ✓ | ✓ | ✓ |
| 12' Hose | - | \checkmark | ✓ | ✓ |
| 9' Hose | ✓ | ✓ | ✓ | ✓ |
| Drum Trolley | - | - | ✓ | ✓ |
| | | | | |
| MOUNT | | | | |
| Side-Mount Bracket | ✓ | ✓ | - | - |
| Top Mount | ✓ | ✓ | ✓ | ✓ |
| Bottom Outlet Mount | - | ✓ | - | ✓ |

KleeBlue"



Closed Tote/IBC **Dispensing Systems**

CONTAMINANT-RESISTANT The closed system dramatically reduces the risk of SCR-engine contamination.

270/330 GALLON READY Pumps can be used on standard 275 and 330 gallon totes/ IBCs.

AUTOMATIC-SHUT OFF Avoid overfilling equipment with an automatic shut-off nozzle.

REGULATE GALLONS The pumps that include meters allow you to keep an closer eye on your DEF usage.

ELECTRIC PUMPS SPECIFICATIONS

- 110 or 12 Volt
- Self-Priming Membrane Pump
- 8 GPM Capability
- Energy-Saving Built-in Timer
- Optional Meter

- 20' Delivery Hose
- Stainless Steel Automatic Shut-Off Nozzle with Swivel End
- Suction Hose
- Tote Side-Mounted Bracket
- Stainless Steel Micro Matic RSV Dispense Coupler for Quick Connection and Drybreak Release

THREE25 ELECTRIC PUMP SPECIFICATIONS

- 120V Heavy-Duty Pump
- 3D DEF Filter
- Piusi DEF Coupler (PDC)
- Metered Automatic Nozzle with Break-Away
- Nozzle and Hose Holder

- Crimped EPDM Delivery Hose
- Stainless Steel Plate with Roll Bar Protection
- Security Lock Bracket System

| PART NUMBER | DESCRIPTION | LIST PRICE | QTY | TOTAL PRICE |
|----------------|---|------------|-----|-------------|
| SBD PPTM-1-110 | 110 Volt Pump with Meter | Call | | |
| SBD PPTM-2-110 | 110 Volt Pump without Meter | Call | | |
| SBD PPT-M-1-12 | 12 Volt Pump with Meter | Call | | |
| SBD PPT-M-2-12 | 12 Volt Pump without Meter | Call | | |
| SBD PI325-120 | Piusi 325 Closed Pump Kit 120v/Metered Nozzle/PDC Coupler/3D Filter | Call | | |
| SBD PI-HP-TKIT | Rotary Hand Pump for Closed Tote-Side Mount | Call | | |
| | | TOTAL | | |



Electric Pump



Open Tote/IBC Dispensing Systems

270/330 GALLON READY Pumps can be used on standard 275 and 330 gallon totes/ IBCs.

AUTOMATIC-SHUT OFF Avoid overfilling equipment with an automatic shut-off nozzle.

REGULATE GALLONS The pumps that include meters allow you to keep an closer eye on your DEF usage.

ELECTRIC PUMPS SPECIFICATIONS

- 110 or 12 Volt
- Self-Priming Membrane Pump
- 8 GPM Capability
- Energy-Saving Built-in Timer
- Optional Meter
- 20' Delivery Hose
- Stainless Steel Automatic Shut-Off Nozzle with Swivel End
- Suction Hose
- Tote Side-Mounted Bracket

GRAVITY KIT SPECIFICATIONS

- 9' Hose
- Manual Nozzle

- Vent
- All Required Fittings

| PART NUMBER | DESCRIPTION | LIST PRICE | QTY | TOTAL PRICE |
|----------------|---|------------|-----|-------------|
| SBD PPT2-110 | Piusi 110v Open Tote Pump Kit (Requires down tube or coupler) | Call | | |
| SBD PPT2-12 | Piusi 12v DC Open Tote Pump Kit (Requires down tube or coupler) | Call | | |
| SBD 330GRAVKIT | Tote Gravity Kit | Call | | |
| | | TOTAL | | |

| PART NUMBER | DESCRIPTION | LIST PRICE | QTY | TOTAL PRICE |
|---------------|-----------------------------------|------------|-----|-------------|
| SBD 910261 | Open Container Down Tube Kit | Call | | |
| SBD PI-K24KIT | Piusi K24 Meter with 90 Deg Elbow | Call | | |
| | | TOTAL | | |



Closed Drum Dispensing Systems

CONTAMINANT-RESISTANT The closed system dramatically reduces the risk of SCR engine contamination.

55 GALLON READY Pumps can be used on standard 55 gallon

AUTOMATIC-SHUT OFF Avoid overfilling equipment with an automatic shut-off nozzle that is available standard with the electric pumps.

REGULATE GALLONS The pumps that include meters allow you to keep a closer eye on your DEF usage.

ELECTRIC PUMPS SPECIFICATIONS

- 110 or 12 Volt
- Self-Priming Membrane Pump
- 8 GPM Capability
- Energy-Saving Built-in Timer
- Optional Meter

ROTARY HAND PUMP SPECIFICATIONS

- 1 Gallon per 10 Revolutions
- RSV Compatible Coupler
- 3/4" Hose

20' Delivery Hose

with Swivel End

Suction Hose

• Polyethylene Ball Valve with Spout

Drum Top-Mounted Bracket

Stainless Steel Automatic Shut-Off Nozzle

 Stainless Steel Micro Matic RSV Dispense Coupler for Quick Connection and Drybreak Release

- Optional Meter

PISTON HAND PUMP SPECIFICATIONS

- 1 Gallon per 11 Down-Strokes
- RSV Compatible Coupler
- Hose
- Dispense Valve

| PART NUMBER | DESCRIPTION | LIST PRICE | QTY | TOTAL PRICE |
|----------------|--|------------|-----|-------------|
| SBD PPDM-1-110 | 110 Volt Pump with Meter | Call | | |
| SBD PPDM-2-110 | 110 Volt Pump without Meter | Call | | |
| SBD PPD-M-1-12 | 12 Volt Pump with Meter | Call | | |
| SBD PPD-M-2-12 | 12 Volt Pump without Meter | Call | | |
| SBD HP-HV-MMP | Rotary Hand Pump with Meter | Call | | |
| SBD HP-HV-MM | Rotary Hand Pump without Meter | Call | | |
| SBD T-HP-MM1 | Piston Hand Pump without Meter | Call | | |
| SBD PI-HP-PKG1 | Rotary Hand Pump Package w/Closed Drum or Tote Coupler | Call | | |

| PART NUMBER | DESCRIPTION | LIST PRICE | QTY | TOTAL PRICE |
|--------------|--|------------|-----|-------------|
| SBD 148-4W | 4-Wheel Drum Trolley | Call | | |
| SBD 148-4W-R | 4-Wheel Drum Trolley with Spring-Rewind Hose Reel & 25' Hose | Call | | |
| SBD KF-KIT | Drum Fill Kit for Trolley | Call | | |
| | | TOTAL | | |



Open Drum Dispensing Systems

55 GALLON READY Pumps can be used on standard 55 gallon drums.

INEXPENSIVE Save money where speed isn't the primary concern.

ELECTRIC PUMPS SPECIFICATIONS

- 110 or 12 Volt
- Self-Priming Membrane Pump
- 8 GPM Capability
- Energy-Saving Built-in Timer
- Optional Meter
- 20' Delivery Hose
- Stainless Steel Automatic Shut-Off Nozzle with Swivel End
- Suction Hose
- Drum Top-Mounted Bracket

ROTARY HAND PUMP SPECIFICATIONS

- 1 Gallon per 10 Revolutions
- Drum Downtube Assembly
- **PISTON HAND PUMP SPECIFICATIONS**
- 1 Gallon per 11 Down-StrokesSuction Tube
- 3/4" Hose
- Polyethylene Ball Valve with Spout
- Optional Meter (As Shown)

- CATTONS
- HoseDispense Valve

■ 2" FNPT Pump Connection

GRAVITY KIT SPECIFICATIONS

- 9' Hose
- Manual Nozzle

- Vent
- All Required Fittings

| PART NUMBER | DESCRIPTION | LIST PRICE | QTY | TOTAL PRICE |
|---------------|--|------------|-----|-------------|
| SBD PPD-2-110 | Piusi 110v Open Drum Pump Kit with Down Tube Kit | Call | | |
| SBD PPD-2-12 | Piusi 12v DC Open Drum Pump Kit with Down Tube Kit | Call | | |
| SBD T-HP-KIT | Piston Hand Pump | Call | | |
| SBD 55GRAVKIT | Drum Gravity Kit | Call | | |
| SBD PI-HP | Piusi Rotary Hand Pump - Open Drums | Call | | |

| PART NUMBER | DESCRIPTION | LIST PRICE | QTY | TOTAL PRICE |
|--------------|--|------------|------|-------------|
| SBD 148-4W | 4-Wheel Drum Trolley | Call | | |
| SBD 148-4W-R | 4-Wheel Drum Trolley with Spring-Rewind Hose Reel & 25' Hose | Call | | |
| SBD KF-KIT | Drum Fill Kit for Trolley | Call | | |
| | | T | OTAL | |



Drum Trolley Option. Shown with Electric (Closed System) Pump