

# Gilbarco Veeder-Root Ergo™75 - 3/4" Retail Prepay Nozzle

## PERFORMANCE IN HAND




Ordering Specifications	
Model #	Description
ER75AGA2	Unleaded Spout - gasoline, up to 10% ethanol With 2 - Step Hold-Open Device - ¾" NPT
ER75ADA2	Leaded Spout - auto-diesel With 2 - Step Hold-Open Device - ¾" NPT





Scuff guard available in the following Pantone colors:



The Ergo™75 nozzle is part of the NEW Ergo™ Series fueling nozzles from Gilbarco Veeder-Root. Sleek. Streamlined. Comfortable. The lightest nozzle ever designed. Purpose-built for easy, one-handed, self service operation. Engineered with stronger materials, tested for 3 million tests cycles, offered with a 24-month warranty. And, above all the lowest pressure drop at 10GPM.

#### **Features**

- Certified UL/ULC 2586 listed for gasoline, diesel, and up to 10% ethanol
- Pressure Sensitive nozzle specifically designed for self-service or card-lock systems with a no-pressure/no flow feature
- Safe unique attitude device feature provides automatic nozzle shut-off safety protection

#### **Designed for Durability**

- Cycle Tested beyond 3 million cycles
- Stronger Materials to extend life of internal moving components
- Reinforced stainless steel spout tip and vac-port sensing tip
- Climate Ready for extreme cold (-40F) and hot (125F) temperatures
- Industry-leading 24-month warranty

#### **Better Flow Performance**

- Lowest pressure drop at 10GPM to sustain higher flow rates
- Dual Poppet for superior flow control to easily regulate low-flow and accurate gasoline dispensing

#### Easiest to Use

- Ergonomic: One-hand operation via hold open clip and, low engagement force and weight
- One-finger hold open clip for an easy true one-handed operation by any user
- ADA compliant with lower lever force required to engage nozzle

#### Other Features

- 2-piece scuff guard for easy replacement
- Splash guard included
- Mates with all 5/8" and 3/4" hoses
- No "remove by date"
- Complimentary splash shield included with all nozzles
- Design working pressure: 50PSI (3.45bar) maximum pressure
- Available in NPT, BSPP and BSPT threads



Construction	
Inlet/Body	3/4" Single Body, Sand Cast Aluminum
Seals and O-rings	Fluorocarbon
Lever/Handguard	Super Tuff Glass Filled Nylon
Spout	Stainless Steel Tip Reinforced Aluminum
Unleaded gas Spout	13/16" OD
Auto Diesel Spout	15/16" OD
Weight	2.15lbs

### **Listings and Certifications**







WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

